



**\*\* IMPORTANT \*\***

T21801 (SHOWN) IS TOP FIX ONLY

FOR BACK OR SIDE FIXING USE T22210 AND INSTALL TO GDP21552

FABRIC WIDTH = SYSTEM WIDTH MINUS 145

FIXINGS FROM SYSTEM TO BUILDING ARE NOT INCLUDED

SEE MANUFACTURERS INSTRUCTION SHEET FOR FITTING THREADED CABLE ENDS

**\*\* IMPORTANT! \*\***

THERE ARE THREE VARIANTS OF THE GUIDE CABLE KIT GDP21495, PROVIDING TWO ALTERNATIVE THREAD LENGTHS :

GDP21495 REF 1 :  
DIM 'A' = 30mm,  
SUPPLIED CABLE LENGTH = 3000mm  
(SUPPLIED FOR SYSTEMS WITH DRAW UP TO 3265mm)

GDP21495 REF 2 :  
DIM 'A' = 60mm,  
SUPPLIED CABLE LENGTH = 6500mm  
(SUPPLIED FOR SYSTEMS WITH DRAW OVER 3265mm)

GDP21495 REF 3 :  
DIM 'A' = 60mm,  
SUPPLIED CABLE LENGTH = 4000mm  
(SUPPLIED FOR SYSTEMS 3265 - 4265mm DRAW)

**\*\* IMPORTANT! \*\***

BACK OR SIDE FIX RETURN PULLEY BRACKET = T22210